



PACKAGING	
Wooden drums	300m & 500m

DESCRIPTION:

Plain annealed stranded copper conductors, PVC insulated AWA, PVC sheath.

APPLICATION:

Power distribution.
Distribution panels and transformers.

SPECIFICATION: SANS 1507-3

Voltage Rating: 600/1000V
Temperature Range: -10°C to 70°C
Sheath colours: Black (Other colours available on request)

TECHNICAL INFORMATION									
CABLE SIZE	NOMINAL STRANDING No. x DIAMETER	APPROX. DIAMETER			CURRENT RATING NOTE 1			VOLT DROP NOTE 1	APPROX. CABLE WEIGHT MASS PER 100M
(mm ²)		(mm)			Ground (A)	Duct (A)	Air (A)	(MV/A/M)	(kg)
		Insulation	AWA	Sheath					
120	37 x 2.03	17.1	1.6	25.7	301	269	314	0.41	178
150	37 x 2.25	19.0	1.6	28.0	336	299	357	0.34	210
185	37 x 2.52	21.2	1.6	30.3	370	329	401	0.29	254
240	61 x 2.25	24.1	1.6	33.3	410	363	481	0.25	311
300	61 x 2.52	26.9	2.0	37.7	476	420	546	0.22	412
400	61 x 2.80	30.3	2.0	42.3	529	465	622	0.20	513
500	61 x 3.20	34.0	2.0	46.0	581	509	695	0.18	620
630	91 x 2.97	37.9	2.5	50.9	623	541	779	0.17	821

Note 1: These ratings are for 2 cables single phase AC or DC clipped direct as per SANS 0142 table 6.2